

## DC142

**Industr. opbouwcontact, schroefaansluiting, wit, schakelafstand  $\pm$  75mm, NC.**

### **Industrial Surface Mount Contact**

---

The DC116 series features a wider make distance and works better on steel without time-consuming installation of brackets. A wider break distance helps prevent false alarms caused by loose fitting doors.

### **Applications**

---

The contacts are used to protect openings such as metal entry/exit doors, overhead doors, roof hatches or hinged skylights.



### **Details**

---

- Rugged design for industrial applications
- Models for use on steel without time-consuming brackets
- Concealed terminals resist tampering and inadvertent shorting
- Easy clamping terminals speed installation
- Mounting screws included

# DC142

Industr. opbouwcontact, schroefaansluiting, wit, schakelafstand  $\pm 75$ mm, NC.

## Technische specificaties

---

### General

Application type	Surface mount
Contact type	NC
Connectivity	Screw

### Wired/wireless

Wired-wireless	Wired
Operating gap	75 mm (max.)

### Physical

Afmetingen	99 x 17 x 15 mm
Colour	Beige



Als een bedrijf van innovatie behoudt Carrier Fire & Security zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar [nl.firesecurityproducts.com](http://nl.firesecurityproducts.com) of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 2 September 2022 - 10:07