

XPR STANDALONE READERS - FEATURES & COMPATIBILITY

	New reference	RS485 output	Prox 125 kHz	MIFARE 13,56 MHz	Green & Red Free LED	Buzzer programming	Backlight ON/OFF	Back Light Dimmer	Remote relays modules compatibility	
									RU1, RU2, RTT & DINRTT	RBO408
Biometry	B100-SA	x				x	x		x	
	B100PROX-EH-SA	x	x			x	x		x	
	B100PROX-MF-SA	x		x		x	x		x	
	B100PAD-SA	x				x	x		x	
	DINB100-SA	x				x	x		x	
Keypad	EX6	x			x	x	x	x	x	x
	EX6P	x	x		x	x	x	x	x	x
	INOX-SA	x				x	x	x	x	x
	MTPADPBK-EH-SA	x	x			x	x	x	x	x
	MTPADS-SA	x				x	x	x	x	x
	MTPADP-BT-EH-SA									
	VKP-SA	x				x	x	x	x	x
Proximity	MINI-SA2		x							
	DINMTPX-SA		x							

XPR OFFLINE READERS - FEATURES & COMPATIBILITY

	New reference	RS485 output	Prox 125 kHz	MIFARE 13,56 MHz	Green & Red Free LED	Buzzer programming	Backlight ON/OFF	Back Light Dimmer	Remote relays modules compatibility	
									RU1, RU2, RTT & DINRTT	RBO408
Proximity	MTPX-MF-SA	x		x			x		x	
	DINMTPX-MF-SA	x		x			x		x	