

MTPADP-RS-MF

KEYPAD AND MIFARE RFID READER WITH
RS-485 OUTPUT

This double technology reader, in black ABS, offers a double access security, including a keypad and a compact 13.56 MHz reader. It can be installed either outside or inside. It comes with a RS485 bus and a backlight keypad. Its LEDs, tamper and buzzer are managed directly by the WS4. It can read Mifare Classic, Desfire and Ultralight.



bx Black Edition

Product available in Black ABS
Ref: MTPADPBK-RS-MF

FEATURES

- Surface mount
- ABS housing
- Colour: Black
- Technology: Keypad + Mifare RFID (13.56 MHz)
- Keys: Backlit metallic
- Reader type: Mifare Classic, Desfire and Ultralight cards
- Read range: up to 5 cm
- RS-485 output
- Green and red LEDs managed by the host *
- 1 internal buzzer (ON/OFF), managed by the host
- Tamper protection: when opened or dismantled
- Push buttons: 1
- Voltage: 9 - 14 V DC
- Current Consumption: 30 mA stand-by;
100 mA maximum.

MECHANICAL CHARACTERISTICS

- IP rating: IP 65
- Operating temperature: -20°C to +50°C
- Operating humidity: 5% to 95% RH without condensation
- Weight: ~0.17 kg
- Dimensions (L x H x W): 51 x 92 x 27 mm



FOBS & CARDS



Ref.	PBX-1E-MS50	PBX-2-MS50	PBX-2C-MS50
Features	ABS Keyfob 13.56MHz	0.75mm ISO Card - 13.56MHz	2mm NISO Card - 13.56MHz

DIMENSIONS

