


## 5E4Z10 Technical Data

Function	Fail-safe
Resistance to forced entry	5.800N
Endurance rating (Cycles)*	200.000
Operating temperature*	-25°C a +70°C
Sound AC (dBA from 50 cm distance)	65 dBA
Sound DC (dBA from 50 cm distance)	5 dBA
DIN 107	DIN R / DIN L
Vertical/Horizontal instalation	Yes
Fixing distance	52,30 mm
Height (Z)	67,70 mm
Width (X)	16 mm
Depth (Y)	28 mm
Keeper	Adjustable
Radian keeper	Internal
Keeper movement	25°
Keeper's depth	5,50 mm
Keeper's adjustability	2 mm
Suitable for fire/smoke protection doors	No
Suitable for outdoor doors	No

\*According to standard EN 14846:2008

### Connection Scheme



### Electrical Characteristics (at 20°C)

Solenoid	Z
Nominal voltage	<b>8-30V AC/DC</b> Tolerance —
Rated resistance	8 Ohms
Duty cycle (%ED)	100%ED (8-30V AC/DC)
Transient voltage suppressor (TVS)	Yes
PCB	
Firmware	—
Hardware	—

### Product certificates

Regulations	(UE) 305/2011
Standards	EN 14846:2008
CPR Certificate	—
Classification	—
Low Voltage Directive	2014/35/UE
(CEM) Directive	2014/30/UE
RoHs Directive	2011/65/UE
REACH Regulation	1907/2006
MPA identifier	—

### Table of Relationship between Voltage (VIN), Current (A) and Preload Force (N)\*

#### Alternating consumption (AC)

VIN (AC)	INITIAL			HOLDING *C2(A)
	*C1(A)	DIN L (N)	DIN R (N)	
6	—	—	—	—
8	0,49	—	—	0,47
9	—	—	—	—
10	—	—	—	—
12	0,63	—	—	0,2
14	—	—	—	—
16	—	—	—	—
22	—	—	—	—
24	0,25	—	—	0,13
28	—	—	—	—
30	0,4	—	—	0,19

#### Direct consumption (DC)

VIN (DC)	INITIAL			HOLDING *C2(A)
	*C1(A)	DIN L (N)	DIN R (N)	
6	—	—	—	—
8	0,28	—	—	0,2
9	—	—	—	—
10	—	—	—	—
12	0,24	—	—	0,15
14	—	—	—	—
16	—	—	—	—
22	—	—	—	—
24	0,1	—	—	0,07
28	—	—	—	—
30	0,09	—	—	0,07

\*C1: Initial Consumption  
\*C2: Holding Consumption

\*The strike processes the opening with preload in less than 1 second.