



## DHUMW C4K (DHB)

### Technical characteristics

|                                |                 |
|--------------------------------|-----------------|
| Installation                   | Surface mounted |
| Holding force                  | 600 N           |
| Finish                         | Black           |
| Certified according to EN 1155 |                 |

|   |   |   |   |   |   |
|---|---|---|---|---|---|
| 3 | 5 | ¾ | 1 | 1 | 3 |
|---|---|---|---|---|---|

|     |               |
|-----|---------------|
| CPR | 0370-CPR-1178 |
|-----|---------------|

|              |       |
|--------------|-------|
| Block Height | 80 mm |
| Block Width  | 80 mm |
| Block Depth  | 46 mm |

|                     |       |
|---------------------|-------|
| Counterplate Height | 80 mm |
| Counterplate Width  | 80 mm |
| Counterplate Depth  | 50 mm |

### Electrical characteristics

|                                    |                                   |
|------------------------------------|-----------------------------------|
| Voltage DC                         | 12/24 V                           |
| Continuous duty DC                 | ED 100%                           |
| Transient Voltage Suppressor (TVS) | Yes                               |
| Rated resistance                   | 60 Ω ..... 12V<br>240 Ω ..... 24V |

|                                      |                                      |
|--------------------------------------|--------------------------------------|
| Current consumption DC (maintenance) | 0,17 A ..... 12V<br>0,08 A ..... 24V |
|--------------------------------------|--------------------------------------|