



ENTRANCE PANEL

AV-04FD

EAN: 5060514913529 (SILVER)

BAS-IP AV-04FD — stylish vandal-proof panels with installation by the flush mount method.

There is also the possibility of individual text or logo appliance on the panel (through in the service center).



SILVER

Main features

- Panel type: Individual.
- Camera: 1/4".
- Resolution: 2 Mpx.
- Camera angle: 100° (horizontal).
- Output video: HD (1280 × 720), H.264 Main Profile.
- Night backlight: 6 LEDs.
- Light sensitivity: 0,01 LuX.
- Protection class: IP65.
- IK-Code: IK09.
- Working temperature: -40 − +65 °C.
- Power consumption: 6.5 W, in standby -3.6 W.
- \bullet Power supply: PoE, +12 \lor DC.
- Body: Aluminum.
- Colors: Silver.
- Dimensions for installation: $85 \times 180 \times 45$ mm.
- Size of the panel: $95 \times 190 \times 27$ mm.
- Installation: Flush mount.



Functionality

- Interface: Multi-language graphical and WEB interface.
- · Lock opening:
 - By means of a monitor
 - By QR code
 - By guest link
 - The BAS-IP Intercom app
 - The BAS-IP Link app
 - From API
- Shortcut buttons: 1 mechanical call button.
- Authentication: Separate password for settings, WEB interface and RTSP stream.
- Talking mode: Full duplex.
- Additionally:
 - Software Link support
 - SIP P2P
 - Built-in relay
 - Open API