

Description

10" IP indoor video entry phone with IPS screen, Wi-Fi, resolution 1280x800 and the ability to connect alarm sensors.

The indoor video entry phone works on the Android 10 operating system.

It comes in 3 color variations: White, Gold, Black and has two installation options: wall mount and flush mount, using a special bracket.

Specifications

Display 10" IPS LCD, capacitive touchscreen

Screen resolution 1280 x 800

Built-in camera Ye

unicia i

Power PoE and + 12 V DC (PSU not included)

Power consumption 6 W, standby 2.5 W

Dimensions 316 x 185 x 27 mm

Colors Black / White / Gold

Body Aluminum

Installation Type Wall mount,

flush mount with special bracket.

Possibilities of connection

Number of individual

Up to 9 panels

panels

Number of multi- Up to 9 panels

apartment panels

Connection of additional Up to 8 monitors

monitors

op to o monitors

Additional connectors

SD card slot (SDHC)

Memory function

Interface

Record photo, video and audio to SD card Multi-language graphical and WEB interface

Number of IP cameras Up to 32 cameras

Main features



10" IPS LCD



Quad splitter



Android OS



Slot for SD card



Lift call



Ability to install third-party apps



Concierge call



Third-party widget support



Downloading custom MP3 ringtones



Software update via Ethernet



High definition video support



Wall and flush mounting installation

Functional capabilities

Number of call ringtones

Download custom MP3 ringtones

Intercom type

Home automation control

Answering machine

Support of receiving messages

Multimedia features Standby mode

Select the type of screensaver

in standby mode

Do Not Disturb Silent mode

Backup photos taken during the call Ability to install third-party applications Support for third-party widgets

Software update

9 melodies to choose

Yes

Video Intercom

Light / curtains / lift

Yes Yes Yes

View video, photo and audio files from an SD card

Yes, customizable by time

 $\label{eq:multi-camera live viewing } \textbf{--} \ \text{up to IP 4 cameras}$

at the same time

Clock Photo frame

Live tour view — up to 16 cameras, time adjustable

Single IP camera live viewing.

Yes, customizable by time Yes, customizable by time

Yes Yes Yes

From the web interface

From SD card

From BAS-IP updates server

Color variations



BLACK



WHITE



GOLD

Appearance and mechanical mounting

