

FMF-ADP-TTY Fire brigade peripheral TTY bus module



The ring bus module FMF-ADP-TTY connects fire brigade peripherals (FBF and FAT) to the fire panel FPA-5000/1200/1100.

Regulatory information

Region	Regulatory compliance/quality marks	
Europe	CE	FMF-ADP-TTY
	CE	FMF-ESPA
	CE	System4000

Installation/configuration notes

For systems with more than 50 activations (for example transmission units, elevator control, smoke dampers, notification appliances) we recommend to use the FPE-5000-UGM module due to performance reasons. For smaller systems the usage of the IOS 0020 A communication module is sufficient.

Parts included

Quantity	Component
1	Ring bus module FMF-ADP-TTY in plastic housing for surface mounting
1	Programming software including OSS license texts
1	Set of cable glands
1	USB cable

- ▶ Fire brigade peripheral ring bus module for FPA-5000/1200/1100
- ▶ TTY/MTS-4A interface for connection to IOS 0020 A or FPE-5000-UGM module
- ▶ Common protocol for FBF and FAT peripherals
- ▶ ESPA interface (optional)

Quantity	Component
1	Product information
1	Additional product label for attachment on housing

Technical specifications

Electrical

Operating voltage	10 V DC to 30 V DC
Current consumption	
FMF-ADP-TTY	50 mA at 24 V DC
FMF-ADP-TTY & FMF-ESPA	53.3 mA at 24 V DC

Mechanics

Dimensions (W x H x D)	182 x 180 x 63 mm
Weight	
• Without packaging	546 g
• With packaging	929 g

Environmental conditions

Permissible operating temperature	-20°C to +60°C
-----------------------------------	----------------

Permissible storage temperature	-20°C to +60°C
Permissible relative humidity	<96% non-condensing
Protection class as per EN 60529	IP66

Ordering information

FMF-ADP-TTY Fire brigade peripheral TTY bus module

FMF-ADP-TTY for FPA-5000/1200/1100

Order number **FMF-ADP-TTY | F.01U.288.669**

Accessories

FMF-ESPA Fire brigade ESPA interface

module with RS232 interface for the FMF-FAT, FMF-FBF-FAT, FMF-FIBS, FMF-ADP-RS232

Order number **FMF-ESPA | F.01U.288.675**

Represented by:

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: + 31 40 2577 284
www.boschsecurity.com/xc/en/contact/
www.boschsecurity.com

Germany:
Bosch Sicherheitssysteme GmbH
Robert-Bosch-Ring 5
85630 Grasbrunn
Tel.: +49 (0)89 6290 0
Fax: +49 (0)89 6290 1020
de.securitysystems@bosch.com
www.boschsecurity.com

North America:
Bosch Security Systems, LLC
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
onlinehelp@us.bosch.com
www.boschsecurity.com

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
www.boschsecurity.com/xc/en/contact/
www.boschsecurity.com