

## DS-PT1-WE(B) Wireless Tag Reader



- 868 MHz two-way wireless communication
- AES-128 encryption
- LED display, show the different feedbacks with easy understanding
- Operation: Stay arm/away arm/disarm by areas
- Arming process with fault confirm, more secure
- Patrol tag check in
- Front and rear panel tamper-proof

## ▪ Specification

Hardware features	
Power switch	Power on/off
Electrical characteristics	
Battery type	3 × AA batteries
Operation humidity	10% to 90% (no condensing)
Operation temperature	-10°C to 55°C (-4°F to +122°F)
Power consumption	Quiescent current: 110 uA Max current: 292 mA Voltage: 1.5 VDC
Battery life span	Up to 2 years (standby time)
Wireless transmission	
RF frequency	868 MHz
RF modulation	2GFSK
RF distance	1200 m (open area)
Display	
Indicator	5, area (blue), fault (orange), arm (blue), disarm (green), alarm (red), signal (red/green)
General	
Installation method	Wall-mounting
Dimension(WxHxD)	75 × 124 × 21 mm
Color	white
Weight	183 g

## ▪ Available Model

DS-PT1-WE(B)

**Headquarters**

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
www.hikvision.com



Follow us on social media to get the latest product and solution information.

