


4MP WiFi Video Doorbell **DH-DB41AB**

Series Overview

The WiFi Video Doorbell is a new addition to the Dahua Wireless series. It not only delivers 2K high-resolution imagery, but also captures more details than conventional fixed lenses through its ultra-wide fisheye lens. The doorbell features passive IR motion detection and transmits videos and audios to mobile devices, allowing you to remotely perform visual confirmation and communicate with visitors. Furthermore, it is compatible with 2.4 GHz Wi-Fi 6 networks, enhancing its connectivity options.



9:41	<u> </u>		
<	Live	0	0-
00	ð	ð	66
T	717		-
A	1/4	5	
Playback	0	•	88
	0 6	\$	P
	^		
Alarm Message		Ē	C
07/05/2023			
 ⇒ R Human Deb 15:01:08 	ection	10.5	
• 판위 Human Det 15:01:05	ection	5	
Control Vehicle Determination Section 25:01:06	ection	10.5	
- vehicle bea	00001	_	

Upgrade Your Experience with DMSS

Dahua Mobile Security Surveillance (DMSS) is a professional remote surveillance management platform that offers remote monitoring, device migration, and sharing. When connected to the internet, the platform provides real-time alerts to improve surveillance efficiency and grant flexibility in security management.









Specifications

1/3" CMOS

Auto

F2.2

Yes

× 720)

DWDR

0°/180°

Yes

Yes

2 (IR LED)

2560 (H) × 1440 (V)

Auto/Manual 1/3 s-1/100,000 s

Up to 10 m (32.81 ft) (IR)

H: 120°; V: 66°; D: 143°

H.265; H.264; H.264H; H.264B

H.264: 32 kbps-8192 kbps

H.265: 32 kbps-8192 kbps

Auto(ICR)/Color/B/W

Main stream: 2560 × 1440@15 fps; 1920 × 1080@15 fps); 1280 × 720@15 fps; sub stream: 640 × 360@25 fps

*The values above are the max. frame rates of each stream; for multiple streams, the values will be

4M (2560 × 1440); 1080p (1920 × 1080); 720p (1280

subjected to the total encoding capacity.

Camera

Lens
Illuminator Number
Illuminator On/Off Control
Illumination Distance
Electronic Shutter Speed
Max. Resolution
Image Sensor

Max. Aperture Field of View

Intelligence

Human Detection

Video

Video Compression

Video Frame Rate

Resolution

Video Bit Rate

Day/Night

WDR

Motion Detection

Image Rotation

Audio

Built-in MIC

What's in the box

X

A



Tools:

Installation Kit × 1 Pin × 1 Mounting Bracket × 1

Documents: Quick Start Guide × 1 Legal and regulation

information × 1 QR Code × 1

Power:

Power Cord × 1

DMSS
iOS;Android
CE-LVD: EN62368-1; CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU; CE-RED: Radio Equipment Directive 2014/53/EU
USB (5 VDC±5%, 2 A) or binding post power supply (10-24 VDC/14-24 VAC, 1.0 A).
Basic: 1.7 W (5 VDC); 2.1 W (10–24 VDC); 2.2 W (14–24 VAC, actve power) Max. (IR + white light + alarm on): 5.3 W (5 VDC); 6.8 W

IEEE 802.11b/g/n/ax 2.4000-2.4835 GHz, 2.4 G,

(10-24 VDC); 6.8 W (14-24 VAC, actve power) Environment

Yes

G.711a

EIRP≤20 dBm

Micro SD card (up to 256 GB)

Operating Temperature

Operating Humidity

Power Consumption

Structure

Built-in Speaker

Network

Mobile Client Certification

Certifications

Power

Power Supply

Wi-Fi

Storage

Audio Compression

Management Software

Casing Material Product Dimensions Net Weight

Plastic 135 mm × 45 mm × 24.2 mm (5.31" × 1.77" × 0.95") $(L \times W \times H)$ 0.11 kg (0.24 lb)

-20 °C to +55 °C (-4 °F to +131 °F)

≤95%

