PFA7751-B

General Others Bracket







Series Overview

The Mounting Bracket works with front-end services, supporting installation methods such as wall mount, pole mount, corner mount and in-ceiling mount. Select brackets are designed to suit complex scenes, making them convenient to use in environments with high temperatures, humidity, frequent vibrations, and in locations that are highly corrosive. These highly reliable brackets are easy to install and use.

Technical Specification


Structure

Casing Material	Plastic	
Product Dimensions	130.2 mm × 40.2 mm × 16.0 mm (5.13" × 1.58" × 0.63") (L × W × H)	
Net Weight	17 g (0.04 lb)	
Gross Weight	25 g (0.06 lb)	
Installation	Wall mount (horizontal 15° angled bracket and mounting bracket)	
Packaging Dimensions	135.0 mm × 44.5 mm × 21.5 mm (5.31" × 1.75" × 0.85") (L × W × H)	
Environment		
Operating Temperature	-40 °C to +60 °C (-40 °F to +140 °F)	
Operating Humidity	10%–90% (RH), non-condensing	
Storage Temperature	-40 °C to +60 °C (-40 °F to +140 °F)	
Storage Humidity	10%–90% (RH), non-condensing	
Anti-corrosion Level	Basic Protection	

Ordering Information

Туре	Model	Description
Bracket	PFA7751-B	General Others Bracket
Accessories (Optional)	PFM900-E	Integrated Mount Tester

Dimensions (mm[inch])



Rev 002.000 © 2025 Dahua. All rights reserved. Design and specificatons are subject to change without notce Pictures in the document are for reference only, and the actual product shall prevail.