

PFA7753-B

General Others Bracket



· Sleek design.

Series Overview

The Mounting Bracket works with front-end services, supporting installation methods such as wall mount, pole mount, corner mount and in-ceiling mount. Select brackets are designed to suit complex scenes, making them convenient to use in environments with high temperatures, humidity, frequent vibrations, and in locations that are highly corrosive. These highly reliable brackets are easy to install and use.

Technical Specification

Structure


Casing Material	Plastic
Product Dimensions	130.2 mm \times 54.0 mm \times 33.0 mm (5.13" \times 2.13" \times 1.30") (L \times W \times H)
Net Weight	22 g (0.05 lb)
Gross Weight	36 g (0.08 lb)
Installation	Wall mount (surface-mounted waterproof bracket)
Packaging Dimensions	$148.0~\text{mm}\times59.5~\text{mm}\times38.5~\text{mm}~(5.83"\times2.34"\times1.52")$ (L × W × H)

Environment

Operating Temperature	-40 °C to +60 °C (-40 °F to +140 °F)
Operating Humidity	10%–90% (RH), non-condensing
Storage Temperature	-40 °C to +60 °C (-40 °F to +140 °F)
Storage Humidity	10%–90% (RH), non-condensing
Anti-corrosion Level	Basic Protection

Ordering Information Type Model Description Bracket PFA7753-B General Others Bracket Accessories (Optional) PFM900-E Integrated Mount Tester

Dimensions (mm[inch])



Rev 002.00

© 2025 Dahua. All rights reserved. Design and specificatons are subject to change without notce Pictures in the document are for reference only, and the actual product shall prevail.